



NOTE: FOR WIRE RANGE AND TORQUE INFORMATION SEE IOM MANUAL.

| MSD PART NUMBER | HP | VOLTAGE | CURRENT | WEIGHT | TERMINAL BLOCK | GROUND LUG |
|-----------------|----|---------|---------|--------|---------------------|-----------------------|
| MSD0055A300 | 40 | 480V | 55 AMPS | 105LBS | WIRE RANGE: 1-22AWG | WIRE RANGE: 2/0-14AWG |

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

| NO | REVISION | DATE | BY | TOLERANCES (EXCEPT AS NOTED) |
|----|----------------------------|-----------|-----|------------------------------|
| F | 3696 ADD DISCHARGE LABEL | 7/29/16 | DSW | DECIMAL |
| E | 3345 ENCLOSURE UPDATED | 9/4/2015 | DSW | .XX +/- .25 |
| D | 3364, 75°C TO 90°C MIN | 6/30/2015 | DSW | .XXX +/- .1 |
| C | 3308 ADD CUSTOMER ENTRANCE | 5/19/15 | DSW | FRACTIONAL |
| B | 3302 CAPS MOVED TO FRONT | 5/6/2015 | DSW | +/- 1/16 |
| A | AS BUILT | 12/11/14 | DSW | ANGULAR |
| NO | | | | +/- 1° |

TCL® W132 N10611 Grant Drive
Germantown, WI 53022

MSD0055A300
MotorShield Sinewave Filter
55 Amps, 480/3/60, Type 1/3R.

DRN BY: DSW DATE: 12/11/14 DWG. No.: 105796DG
SCALE: 1/4 APRVD. SHEET 1 OF 1