



MSD PART NUMBER	HP	VOLTAGE	CURRENT	APPROX. WEIGHT	PRESSURE TERMINAL WIRE RANGE
MSN0850A300	700	480V	850 AMPS	850 LBS	(4) 350MCM-6AWG

NOTE: FOR TERMINAL TORQUE
SEE IOM MANUAL.

CUSTOMER IS RESPONSIBLE FOR INSTALLATION
TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.

TOLERANCES (EXCEPT AS NOTED)			
DECIMAL			
	.XX ± .25		
	.XXX ± .10		
FRACTIONAL			
	± 1/16		
ANGULAR			
	± 1°		
B	6175 Add Fan Tray	02/13/23	JRN
A	As Designed	07/14/15	BWM
NO	REVISION	DATE	BY

W132N10611 Grant Drive
Germantown, WI 53022
© 2023 TCI, LLC

An Allied Motion Company

MSN0850A300, Motorshield Sinewave Filter
480/3/60, Type 1/3R

DRN BY BWM DATE 07/14/15 SIZE 106314DG
SCALE 1/10 APRVD: C

SHT. 1 OF 1