



NOTE: FOR WIRE RANGE AND TORQUE INFORMATION SEE IOM MANUAL.

MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	TERMINAL BLOCK	GROUND LUG
MSD0005B300	1	240V	5 AMPS	57LBS	WIRE RANGE: 1-22AWG	WIRE RANGE: 1/0 -14AWG
MSD0007B300	2	240V	7 AMPS	58LBS	WIRE RANGE: 1-22AWG	WIRE RANGE: 1/0 -14AWG
MSD0010B300	3	240V	10 AMPS	58LBS	WIRE RANGE: 1-22AWG	WIRE RANGE: 1/0 -14AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

Ø.44 DIA Holes  
4 Places

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.						TOLERANCES (EXCEPT AS NOTED) DECIMAL .XX ± .03 .XXX ± .010 FRACTIONAL ± 1/32 ANGULAR ± 1°		 W132N10611 (Rev 13 Feb 2022) Germantown, WI 53022 © 2022 TCI, LLC An Official Motors Group Company Motor Shield Sinewave Filter 5 to 10 Amps, 240/3/60, Type 1/ 3R DWN BY: BSW DATE: 12/17/14 SCALE: DRAWN: 107523DG FILE:	
A	As Designed	12/29/17	JRN						
NO	REVISION	DATE	BY						