



NOTE: FOR WIRE RANGE AND TORQUE INFORMATION SEE IOM MANUAL.

MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	TERMINAL BLOCK	GROUND LUG
MSD0028B300	10	240V	28 AMPS	105LBS	WIRE RANGE: 1-22AWG	WIRE RANGE: 2/0-14AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.	NO	REVISION	DATE	BY	± 1°	TOLERANCES (EXCEPT AS NOTED) DECIMAL .XX ± .03 .XXX ± .010 FRACTIONAL ± 1/32 ANGULAR ± 1°	W132N10611 (Rev 11/16) Germantown, WI 53022 © 2022 TCI, LLC MSD0028B300 MotorShield Sinewave Filter 28A, 240/3/60, Type 1/3R DESIGNED BY: JRN DATE: 1/18/18 DRAWN BY: JRN DATE: 1/18/18 SCALE: 1:4.25 SHEET: 1 OF 1
	A	As Designed	01/18/18	DSW			
	NO						